

AGRIMAX FORTIS - Technical Specifications



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	600/70 R 34
LI/SS	160 D/163 A8

Dimensions US Standard

Usa code	94035649
Section Width (inch)	23.3
Overall Diameter (inch)	67.1
Static Loaded Radius (inch)	30
Rolling Circumference (inch)	201.1
Rim Rec	DW 18 L
Rim Alt	DW 20 B ; W 18 L
ECE	E4-106R-001401
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	4760	5560	6250	6940	7640	8230	9130	9920
30	5000	5840	6570	7300	8020	8650	9590	10420
25	5160	6020	6780	7530	8280	8930	9890	10750
20	5480	6390	7200	7990	8780	9480	10500	11410
5 LT	6380	7450	8380	9310	10240	11030	12230	13290
5 HT	5480	6390	7200	7990	8780	9480	10500	11410

Printed on 08/08/2024 03:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..