

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	180/95 R 16 (6.50 R 16)
LI/SS	105 A8/B

Dimensions International Standard

Section Width (mm)	185
Overall Diameter (mm)	760
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2265
SRI (mm)	350
Rim Rec	5.5 F
Rim Alt	6.0 F
ECE	E4-106R-000756
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	430	550	670	735	790	865	925	-
40	430	550	670	735	790	865	925	-
30	460	585	715	785	845	925	990	-
10	505	655	795	950	1085	1130	1255	1390

Printed on 08/08/2024 06:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..