

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/80 R 18
LI/SS	125 A8/125 B

Dimensions International Standard

Section Width (mm)	250
Overall Diameter (mm)	835
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2539
SRI (mm)	410
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E11-106R-006605
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
40	580	680	780	875	975	1060	1175	1240	1355	1470	1570	1650
30	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770
10 LT	780	910	1045	1175	1310	1420	1575	1665	1820	1975	2105	2215
10 HT	620	730	835	940	1045	1135	1260	1330	1455	1580	1685	1770

Printed on 13/07/2024 11:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..