

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	250/85 R 22
LI/SS	113 A8/B

Dimensions International Standard

TKPH	1
Section Width (mm)	251
Overall Diameter (mm)	985
Static Loaded Radius (mm)	453
Rolling Circumference (mm)	2964
SRI (mm)	475
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-002973
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	545	625	715	805	900	990	1070	1150
40	545	625	715	805	900	990	1070	1150
30	585	670	770	865	965	1065	1150	1235
10 LT	730	835	960	1085	1210	1330	1440	1545
10 HT	585	670	770	865	965	1065	1150	1235

Printed on 08/08/2024 07:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..