

## AGRIMAX RT 855 - Technical Specifications



### Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	250/85 R 22 (9.5 R 22)
LI/SS	113 A8/B

## Dimensions US Standard

Usa code	94049332
Section Width (inch)	9.9
Overall Diameter (inch)	38.8
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	116.7
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-002973
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Printed on 13/07/2024 11:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..