

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	280/85 R 28 (11.2 R 28)
LI/SS	118 A8/B

Dimensions International Standard

Section Width (mm)	292
Overall Diameter (mm)	1187
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3558
SRI (mm)	575
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-000614
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	730	845	965	1085	1205	1320
40	730	845	965	1085	1205	1320
30	780	910	1035	1165	1290	1415
10 LT	975	1135	1295	1455	1615	1770
10 HT	780	910	1035	1165	1290	1415

Printed on 18/07/2024 03:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..