

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	320/85 R 28 (12.4 R 28)
LI/SS	124 A8/B

Dimensions US Standard

Usa code	94047352
Section Width (inch)	13
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	147.4
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000615
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3520
25	1940	2260	2580	2900	3220	3520
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780

Printed on 13/07/2024 10:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..