

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	SPECIAL
Type	TL
Tyre Size	340/85 R 24 (13.6 R 24)
LI/SS	125 A8/B

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1188
Static Loaded Radius (mm)	531
Rolling Circumference (mm)	3540
SRI (mm)	575
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000604
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	910	1060	1205	1355	1505	1650
40	910	1060	1205	1355	1505	1650
30	975	1135	1295	1455	1615	1770
10 LT	1220	1420	1620	1820	2020	2215
10 HT	975	1135	1295	1455	1615	1770

Printed on 08/08/2024 08:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..