

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 28 (13.6 R 28)
LI/SS	139 A8/B

Dimensions International Standard

Section Width (mm)	353
Overall Diameter (mm)	1315
Static Loaded Radius (mm)	603
Rolling Circumference (mm)	3963
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-008233
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	950	1120	1290	1435	1605	1750	1920	2070	2260	2430
40	950	1120	1280	1435	1605	1750	1920	2070	2260	2430
30	1020	1200	1385	1540	1720	1880	2060	2215	2425	2605
10 LT	1275	1500	1730	1925	2155	2350	2580	2775	3035	3260
10 HT	1020	1200	1385	1540	1720	1880	2060	2215	2425	3490

Printed on 18/07/2024 03:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..