

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	380/85 R 34 (14.9 R 34)
LI/SS	137 A8/B

Dimensions International Standard

Section Width (mm)	380
Overall Diameter (mm)	1509
Static Loaded Radius (mm)	682
Rolling Circumference (mm)	4504
SRI (mm)	725
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-000655
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1265	1475	1680	1890	2095	2300
40	1265	1475	1680	1890	2095	2300
30	1360	1580	1800	2025	2245	2465
10 LT	1700	1975	2255	2530	2810	3085
10 HT	1360	1580	1800	2025	2245	2465

Printed on 08/08/2024 07:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..