

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	520/85 R 42 (20.8 R 42)
LI/SS	167 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	1951
Static Loaded Radius (mm)	858
Rolling Circumference (mm)	5782
SRI (mm)	925
Rim Rec	DW 16 L ; W 16 A ; DD 16
Rim Alt	DW 18 A ; DD 18 ; W 18 A ; DD 18 L
ECE	E4-106R-001491
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.4	2.8	3.2
50	2270	2640	3015	3385	3755	4125	4635	5070	5450
40	2270	2640	3015	3385	3755	4125	4635	5070	5450
30	2430	2830	3225	3625	4020	4415	4960	5425	5830
10 LT	3045	3540	4040	4535	5035	5530	6210	6795	7305
10 HT	2430	2830	3225	3625	4020	4415	4960	5425	5830

Printed on 08/08/2024 12:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..