

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	210/95 R 28 (8.3 R 28)
LI/SS	116 A8/B

Dimensions US Standard

Usa code	94042548
Section Width (inch)	8.4
Overall Diameter (inch)	43.7
Static Loaded Radius (inch)	20.2
Rolling Circumference (inch)	132.4
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001819
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
30	1300	1490	1710	1930	2150	2370	2570	2760	-
25	1300	1490	1710	1930	2150	2370	2570	2760	-
20	1390	1600	1840	2070	2310	2550	2760	2950	-
5	1910	2190	2450	2690	2980	3270	3800	4010	4130

Printed on 08/08/2024 06:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..