

## AGRIMAX RT 955 - Technical Specifications



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	230/95 R 42 (9.5 R 42)
LI/SS	133 A8/B

Dimensions US Standard

Usa code	94028610
Section Width (inch)	9
Overall Diameter (inch)	59.3
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	180.9
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000772
TRA Code	R1

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
25	1770	2330	2820	3100	3270	3590	3910	4230	4530	-
20	1900	2480	3020	3310	3510	3850	4190	4530	4860	-
5	2120	2670	3270	3890	4500	4640	5180	5730	6270	6810

Printed on 08/08/2024 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..