

AGRIMAX SPARGO - Technical Specifications



Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer

Version	STANDARD
Type	TL
Tyre Size	VF 320/90 R 54 CFO
LI/SS	168 D

Dimensions US Standard

Usa code	94075249
Section Width (inch)	12.7
Overall Diameter (inch)	76.7
Static Loaded Radius (inch)	35.8
Rolling Circumference (inch)	234.1
Rim Rec	W 11
Rim Alt	W 10 ; DW 10 ; W 10 L ; DW 11
ECE	E11-106R-009070
TRA Code	R1

Load capacity (lbs)

mph / psi	14	17	20	23	26	29	32	35	38	41	44	47	49	52	55	58	61	64
45	4920	5490	6180	6750	7090	7430	7670	7890	8290	8690	9030	9370	9660	9950	10230	10520	10970	11420
From 40 to 25	5320	5940	6670	7290	7670	8030	8280	8530	8960	9400	9760	10130	10440	10750	11060	11370	11870	12350
20	5430	6060	6820	7450	7820	8190	8450	8700	9140	9580	9960	10340	10650	10970	11280	11600	12110	12600
12	5530	6180	6950	7590	7970	8360	8610	8870	9320	9770	10160	10540	10860	11180	11500	11820	12340	12850
5	5850	6530	7350	8020	8430	8830	9110	9390	9860	10330	10740	11150	11490	11820	12160	12500	13040	13580

Printed on 17/09/2024 08:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..