

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 46
LI/SS	174 D

Dimensions International Standard

Section Width (mm)	715
Overall Diameter (mm)	2041
Static Loaded Radius (mm)	896
Rolling Circumference (mm)	6092
SRI (mm)	975
Rim Rec	DW 25 B
Rim Alt	DW 27 B
ECE	E11-106R-0010941
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6
70	3355	3905	4455	5005	5555	6100
from 65 to 40	3685	4290	4895	5495	6100	6700
30	3760	4375	4990	5605	6220	6835
20	3835	4465	5090	5720	6345	6970
10	4055	4720	5385	6045	6710	7370
*Upto 10 Cyc with front loader	5160	6005	6850	7695	8540	9380
10HT	3760	4375	4990	5605	6220	6835

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/04/2025 03:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..