



## AS 505 - Data Sheet



### Description

AS 505 is best suited for soil tillage operations with trailers and implement machinery. It features excellent self-cleaning properties and increased traction on the ground, especially on muddy soil. The tire also ensures a long tire life-cycle.

### UM

International Standard

### Construction

BIAS

### Machinery

Agriculture: Implement Machinery • Trailer

SIZE	Version	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
6.5/80 - 15	STANDARD	92 A8	104 A8	8	5.0	4½ K ; 5 K ; 5 J	171	695	325	2106	TL	E4-106R-002660
6.5/80 - 15	STANDARD	86 A8	98 A8	6	5.0	4½ K ; 5 K ; 5 J	171	695	325	2106	TL	E4-106R-002188

Printed on 13/07/2024 12:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..