

AW 705 - Technical Specifications



Description

AW 705 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. It is ideal for modern farming thanks to improved durability and high load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	400/55 - 22.5
LI/SS FREE ROLLING	156 A8

Dimensions International Standard

Ply Rating	20
Section Width (mm)	405
Overall Diameter (mm)	1016
Static Loaded Radius (mm)	443
Rolling Circumference (mm)	3072
Rim Rec	AG 11.75
Rim Alt	12.25 ; AG 13.00

Load capacity (Kg)

	km/h / bar	5.00
	10 FR	5600
	25 FR	4760
	30 FR	4480
	40 FR	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 17:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..