

EM 936 LOADER SPECIAL - Technical Specifications



Description

EM 936 LOADER SPECIAL has been specially designed for telehandlers in loading applications. It features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20 (405/70 - 20)
LI/SS	149 B

Dimensions International Standard

Ply Rating	14
Overall Width (mm)	405
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	480
Rolling Circumference (mm)	3295
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

Load capacity (Kg)

km/h / bar	3.50
50	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 17:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..