

## EM 936 - Technical Specifications



### Description

EM 936 has been specially designed for excavators and telehandlers in digging and loading operations. Besides, one size is particularly suitable for graders and loaders in grading, loading and transport applications. EM 936 features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions. Its "special" version is made of a special compound.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrial: Excavator • Telehandler

Version	SPECIAL
Type	TL
Tyre Size	16.0/70 - 20 (400 / 70 -20)
LI/SS	149 B/166 A2

## Dimensions US Standard

Usa code	94049325
Ply Rating	14
Overall Width (inch)	15.9
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	129.7
Rim Rec	13 SDC
Rim Alt	13
TRA Code	E2

## Load capacity (lbs)

mph / psi	51	65
30	7160	-
5	-	11680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 15:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..