



FARM SPECIAL - Data Sheet



Description

FARM SPECIAL is a tractor tire suitable for soil tillage operations. The strong casing provides a high level of puncture resistance and a longer service life, whilst the rounded shoulders prevent soil damages ensuring the protection of the valuable crops. FARM SPECIAL features a unique tread design with special mud breakers for best self-cleaning properties. In addition, dual angled lugs provide excellent traction and reduced slippage.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	TKPH	ECE
11.2 - 24	STANDARD	R1	116 A6	8	W 10	W 9	285	1095	509	3283		TT		E11-106R-005528
12.4 - 24	STANDARD	R1	121 A6	8	W 11	W 9 ; W 10	320	1155	534	3504	550	TT		E11-106R-005529
13.6 - 24	STANDARD	R1	123 A6	8	W 12	W 11	350	1205	554	3635		TT		E11-106R-005530
14.9 - 24	STANDARD	R1	128 A6	8	W 13	W 11 ; W 12	378	1255	572	3775	600	TT		E11-106R-005531
9.5 - 24	STANDARD	R1	112 A6	8	W 8	W 7	240	1050	491	3194		TT		E11-106R-005527
11.2 - 28	STANDARD	R1	118 A6	8	W 10	W 9	285	1205	563	3694	575	TT		E11-106R-005532
12.4 - 28	STANDARD	R1	123 A6	8	W 11	W 9 ; W 10	315	1265	589	3853	600	TT		E11-106R-005533
13.6 - 28	STANDARD	R1	125 A6	8	W 12	W 11	350	1310	610	3985	625	TT		E11-106R-005534
14.9 - 28	STANDARD	R1	130 A6	8	W 13	W 11 ; W 12	375	1355	620	4105	650	TT		E11-106R-005535
16.9 - 30	STANDARD	R1	137 A6	8	W 15 L	W 14 L	431	1469	671	4456		TT		E11-106R-005536
18.4 - 30	STANDARD	R1	139 A6	8	W 16 L	W 15 L	451	1533	689	4599		TT		E11-106R-005537
12.4 - 32	STANDARD	R1	124 A6	8	W 11	W 9 ; W 10	320	1360	634	4137		TT		E11-106R-005538
13.6 - 36	STANDARD	R1	129 A6	8	W 12	W 11	345	1515	704	4591		TT		E11-106R-005539
13.6 - 38 (14.00 - 38)	STANDARD	R1	131 A6	8	W 12	W 11	345	1565	736	4874	750	TT	1	E11-106R-005540
14.00 - 38 (13.6 - 38)	STANDARD	R1	131 A6	8	W 12	W 11	345	1565	736	4874	750	TT		E11-106R-004381
15.5 - 38	STANDARD	R1	133 A6	8	W 14 L		394	1575	731	4813		TT		E11-106R-005541

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 20:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..