

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	580/65 R 22.5
LI/SS	166 D

Dimensions International Standard

Section Width (mm)	577
Overall Diameter (mm)	1326
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	4058
SRI (mm)	625
Rim Rec	AG 18.00
Rim Alt	AG 16.00 ; AG 17.00 ; AG 20.00
ECE	E4-106R-001416

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1560	1805	2050	2440	2880	3295	3660	4095	4485	4875
65	1700	1965	2230	2650	3130	3580	3975	4455	4880	5300
50	2055	2375	2695	3210	3785	4335	4815	5390	5905	6415
40	2310	2670	3030	3605	4255	4870	5410	6060	6635	7210
25	2680	3100	3520	4190	4945	5655	6285	7035	7705	8375
10	3055	3535	4010	4770	5630	6440	7155	8015	8780	9540

Printed on 07/08/2024 23:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..