

## FL 630 SUPER - Technical Specifications



### Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	650/65 R 26.5
LI/SS	174 D

Dimensions US Standard

Usa code	94045587
Section Width (inch)	25.4
Overall Diameter (inch)	59.8
Static Loaded Radius (inch)	26.9
Rolling Circumference (inch)	183.2
Rim Rec	AG 20.00
ECE	E4-106R-001651

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4310	4980	5650	6870	7940	9150	10360	11170	12380	13450
40	4730	5470	6210	7540	8720	10050	11380	12270	13590	14770
30	5730	6620	7520	9130	10550	12160	13770	14850	16460	17880
25	6440	7440	8440	10250	11860	13670	15480	16690	18500	20090
15	7470	8640	9810	11920	13780	15880	17980	19380	21480	23350
5	8510	9840	11180	13570	15700	18090	20480	22070	24470	26590

Printed on 07/08/2024 21:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..