

FL 630 SUPER - Technical Specifications



Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	750/60 R 26.5
LI/SS	180 D

Dimensions International Standard

Section Width (mm)	754
Overall Diameter (mm)	1574
Static Loaded Radius (mm)	694
Rolling Circumference (mm)	4800
SRI (mm)	725
Rim Rec	AG 24.00
ECE	E4-106R-001427

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2340	2705	3070	3725	4310	4965	5625	6060	6720	7300
65	2560	2960	3360	4080	4720	5440	6160	6640	7360	8000
50	3100	3585	4070	4940	5715	6585	7455	8035	8910	9680
40	3485	4030	4570	5550	6420	7400	8380	9035	10010	10880
25	4045	4680	5310	6450	7460	8600	9735	10495	11630	12640
10	4610	5330	6050	7345	8500	9795	11090	11955	13250	14400

Printed on 07/08/2024 23:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..