

LIFTMAX LM SMOOTH - Technical Specifications



Description

LIFTMAX LM SMOOTH has been specifically engineered for empty container handlers, but it is also suitable for heavy load lift trucks and forklifts. Its smooth tread pattern provides a uniform weight distribution across the complete contact area and avoids base lug cracking. The unique tread compound ensures excellent wear and a long service life. LIFTMAX LM SMOOTH is perfect for logistics operations on hard surfaces, especially on asphalt. The strong All Steel casing and the reinforced sidewall ensure maximum stability and optimum handling during lift mode. In addition, the radial casing absorbs surface irregularities resulting in improved riding comfort and reduced operator fatigue. Being antistatic-compliant LIFTMAX LM SMOOTH is capable of dissipating static charge from the vehicle.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Container Handler • Forklift

Version	INDUSTRIAL
Type	TL
Tyre Size	14.00 R 24
LI/SS	193 A5

Dimensions International Standard

Overall Width (mm)	388
Overall Diameter (mm)	1415
Rim Rec	10.00W
Rim Alt	10.0, 10.00WA

Load capacity (Kg)

km/h / bar	10.00
25	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 17:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..