



LP 450 - Data Sheet



Description

LP 450 is a road-oriented tire for low platforms in transport applications. This high-speed tire provides significant fuel savings as well as an extended tire life-cycle.

UM

International Standard

Construction

BIAS

Machinery

Industrial: Low Platform Trailer

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
8 - 14.5	STANDARD	12	6.00 MH		214	710	321	2109	TL
9 - 14.5	STANDARD	14	7.00 MH		246	712	322	2115	TL
9 - 14.5	STANDARD	12	7.00 MH		246	712	322	2115	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 17:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..