

MUD POWER HD - Technical Specifications



Description

MUD POWER HD has been specifically engineered for skid steers. Its deep tread design along with the special lug pattern provides excellent traction on wet and soft soil. MUD POWER HD is made of a special industrial compound and features a strong nylon casing resulting in an extended tire life-cycle even under severe conditions.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	315
Overall Diameter (mm)	850
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2514
Rim Rec	9.75
ECE	E11-106R-005563
TRA Code	R4

Load capacity (Kg)

	km/h / bar	4.50
	10	2540
	15	2005
	25	1855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 17:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..