

# MULTIMAX MP 527 - Technical Specifications



## Description

MULTIMAX MP 527 is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications. The tire shows a block pattern design providing excellent traction even on the harder surfaces. The strong sidewall ensures outstanding stability in lift mode. MULTIMAX MP 527 is made of a special cut-and-chip-resistant compound providing and a long service life.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler  
Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	480/80 R 26 IND
LI/SS	160 A8/B

## Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1428
Static Loaded Radius (mm)	642
Rolling Circumference (mm)	4259
SRI (mm)	675
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-004069

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.2	2.4	2.6	2.8	3.2	3.2	3.4	3.6
50	2610	3060	3330	3555	3780	4005	4275	4500	-	-
40	2610	3060	3330	3555	3780	4005	4275	4500	-	-
30	2795	3275	3565	3805	4045	4290	4575	4815	-	-
25	2900	3400	3700	3950	4200	4450	4750	4995	-	-
10 Cyc.	3175	3915	4255	4590	4995	5335	5670	6075	6415	6750
Static	4865	6005	6525	7040	7660	8180	8695	9315	9835	10350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 15:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..