

MULTIMAX MP 529 - Technical Specifications



Description

MULTIMAX MP 529 is a steel belted multi-purpose radial tire designed for telehandlers in industrial applications. Its tread design has been specially developed for hard surfaces. The strong sidewall and the larger footprint area ensure outstanding stability in lift mode. MULTIMAX MP 529 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

UM

International Standard

Construction

RADIAL

Machinery

Industrial: Telehandler

Version	STEEL BELTED
Type	TL
Tyre Size	400/70 R 20 IND (405/70R20)
LI/SS	149 A8/B

Dimensions International Standard

Section Width (mm)	415
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3314
SRI (mm)	525
Rim Rec	13
Rim Alt	12 SDC;13SDC;14
ECE	E11-106R-0010769

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.2	4.4
50	1550	1825	2100	2375	2650	2950	3250	-	-
40	1550	1825	2100	2375	2650	2950	3250	-	-
30	1660	1960	2265	2570	2870	3175	3480	-	-
25	1730	2040	2355	2670	2980	3295	3610	-	-
10 Cyc.	1910	2335	2760	3180	3605	4030	4455	4670	4880
Static	2930	3580	4230	4880	5530	6180	6830	7155	7480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 18:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..