

RIB TRAILER - Technical Specifications



Description

RIB TRAILER is a bias tire specially designed for on & off the road applications with implement machinery, particularly straw reapers.

Its 4-rib design optimizes load distribution, and the strong casing ensures stubble resistance. RIB TRAILER has been designed with a special compound that ensure an excellent tire life thanks to its high wear resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TT
Tyre Size	7.00 - 19
LI/SS	119 A3

Dimensions International Standard

Ply Rating	10
Section Width (mm)	210
Overall Diameter (mm)	875
Rim Rec	5.00

Load capacity (Kg)

km/h / bar	5.15
15	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 17:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..