

RIDEMAX FL 615 - Technical Specifications



Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STEEL BELTED
Type	TL
Tyre Size	VF800/65 R 32
LI/SS	190 D
LI/SS DRIVE WHEEL	190 D
LI/SS FREE ROLLING	190 D

Dimensions US Standard

Usa code	94513925
Section Width (inch)	32.1
Overall Diameter (inch)	72.8
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	220.9
Rim Rec	DW 28 B
ECE	E11-106R-0010408

Load capacity (lbs)

mph / psi	15	17	23	29	35	41
40	11450	12850	15660	17770	20570	23370
30	13400	15050	18330	20790	24070	27350
25	14780	16590	20200	22920	26530	30150
20	16160	18130	22090	25050	29010	32960
15	16730	18770	22870	25940	30040	34130
10	17420	19540	23810	27010	31270	35530
5	18780	21090	25680	29130	33730	38330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/04/2025 02:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..