

RIDEMAX FROST - Data Sheet



Description

RIDEMAX FROST is engineered by BKT for tractors operating in transport and municipal maintenance during snow and ice conditions. With a cold-resistant, specially formulated compound, the tire maintains flexibility and elasticity even at sub-zero temperatures, ensuring optimal grip in extreme winter environments. The tread, featuring multiple sipes, delivers excellent traction on snowy and icy surfaces, creating micro-edges and partial vacuum in the slit that improve grip and reduce the risk of slippage. Additionally, the tread design incorporates snow, utilizing snow-to-snow adhesion to further enhance traction. The compound, made from natural rubber and specific additives, ensures the tire remains flexible and durable in harsh conditions. These specialized compounds also protect the rubber from degradation caused by low temperatures, UV rays, and ozone, prolonging the tire's lifespan. Silica reinforcements increase resistance to cuts and tears on rough or icy terrain, without compromising flexibility. Moreover, RIDEMAX FROST provides superior driving comfort, reducing vibrations and driver fatigue, ensuring safe and efficient operations even during long working hours in winter.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Tractor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
540/80 R 38 IND	STEEL BELTED	172A8/167D	DW 18 L	DW 16 L	550	1835	842	5591	875	TL	E11-106R-0010575

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 06:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..