

SKID POWER HD (A) - Technical Specifications



Description

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

UM

US Standard

Construction

BIAS

Machinery

Industrial: Skid Steer

Version	STANDARD
Type	TL
Tyre Size	385/50 - 15

Dimensions US Standard

Usa code	94075904
Ply Rating	8
Section Width (inch)	14.8
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	88.2
Rim Rec	13 LB

Load capacity (lbs)

mph / psi	45
10	3650
20	2645

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..