

## SR 713 - Technical Specifications



### Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	VF 445/65 R 22.5
LI/SS	169 D

## Dimensions US Standard

Usa code	94059416
Overall Width (inch)	17.3
Overall Diameter (inch)	45.7
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	138.4
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-106R-005501
TRA Code	I1

## Load capacity (lbs)

mph/psi	35	38	41	44	46	49	52	55	58	61	64
0	18055	18975	20240	21505	22195	23460	24150	25300	26910	27600	29440
5	14130	14850	15840	16830	17370	18360	18900	19800	21060	21600	23040
10	13580	14275	15225	16175	16695	17645	18165	19030	20240	20760	22145
15	12405	13035	13905	14775	15245	16115	16590	17380	18485	18960	20225
20	11855	12460	13290	14120	14570	15400	15855	16610	17665	18120	19330
25	10675	11220	11970	12715	13125	13870	14280	14960	15910	16320	17410
30	9500	9985	10650	11315	11675	12340	12705	13310	14155	14520	15490
35	8400	8830	9415	10005	10325	10915	11235	11770	12520	12840	13695
40	7850	8250	8800	9350	9650	10200	10500	11000	11700	12000	12800
43	7145	7510	8010	8510	8780	9280	9555	10010	10645	10920	11650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 17:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..