

TF 8181 - Technical Specifications



Description

TF 8181 is a field and road tire designed for 2WD tractors in soil tillage and haulage applications. This tire provides excellent steering performance.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: 2WD Tractor Industrial: Trailer

| Version | SPECIAL |
|-----------|-----------|
| Туре | ΤΤ |
| Tyre Size | 7.50 - 18 |
| LI/SS | 97 A8 |

Dimensions US Standard

| Usa code | 94057122 |
|------------------------------|----------|
| Ply Rating | 6 |
| Section Width (inch) | 8.2 |
| Overall Diameter (inch) | 34.4 |
| Static Loaded Radius (inch) | 16.1 |
| Rolling Circumference (inch) | 102.6 |
| Rim Rec | 5.50 F |
| TRA Code | F2 |

Load capacity (lbs)

| mph / psi | 44 |
|-----------|------|
| 25 | 1610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 21:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..