

TR 273 - Data Sheet



Description

TR 273 is a tractor tire suitable for soil tillage and specifically designed to provide maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning properties. TR 273 perfectly meets all these characteristics.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | TKPH | ECE |
|-----------|----------|----------|--------|----|-------------------|-----------------|-----|------|-----|------|------|------|-----------------|
| 12.4 - 24 | STANDARD | R2 | 121 A6 | 8 | W 11 | W 10 | 315 | 1195 | 550 | 3722 | TT | 0 | E11-106R-004100 |
| 13.6 - 24 | STANDARD | R2 | 123 A6 | 8 | W 12 | W 11 | 350 | 1240 | 570 | 3795 | TT | 1 | E11-106R-005252 |
| 14.9 - 24 | STANDARD | R2 | 128 A6 | 8 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | TT | | E11-106R-004514 |
| 14.9 - 24 | STANDARD | R2 | 132 A6 | 10 | W 13 | W 12 | 380 | 1310 | 595 | 4044 | TT | | E11-106R-004515 |
| 18.4 - 26 | STANDARD | R2 | 146 A6 | 12 | W 16 | W 15 | 470 | 1490 | 673 | 4534 | TT | 1 | E11-106R-005314 |
| 23.1 - 26 | STANDARD | R2 | 156 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-004628 |
| 23.1 - 26 | STANDARD | R2 | 149 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-003620 |
| 23.1 - 26 | STANDARD | R2 | 153 A6 | 12 | DW 20 A ; DW 20 B | | 590 | 1655 | 737 | 5053 | TT | | E11-106R-003395 |
| 14.9 - 28 | STANDARD | R2 | 130 A6 | 8 | W 13 | W 12 | 385 | 1410 | 651 | 4368 | TT | | E11-106R-004516 |
| 16.9 - 30 | STANDARD | R2 | 143 A6 | 12 | W 15 L | W 14 L | 435 | 1530 | 706 | 4800 | TT | 1 | E11-106R-005315 |
| 18.4 - 30 | STANDARD | R2 | 149 A6 | 12 | W 16 L | W 15 L | 465 | 1585 | 723 | 4924 | TT | | E11-106R-003621 |
| 23.1 - 30 | STANDARD | R2 | 157 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1748 | 794 | 5356 | TT | 0 | E11-106R-003645 |
| 23.1 - 30 | STANDARD | R2 | 151 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1748 | 794 | 5356 | TT | | E11-106R-003622 |
| 18.4 - 34 | STANDARD | R2 | 150 A6 | 12 | DW 16A | W16L,W15L,DW15L | 475 | 1701 | 775 | 5253 | TT | | E11-106R-004517 |
| 23.1 - 34 | STANDARD | R2 | 160 A6 | 14 | DW 20 A ; DW 20 B | | 590 | 1850 | 833 | 5634 | TT | 1 | E11-106R-003646 |
| 23.1 - 34 | STANDARD | R2 | 153 A6 | 10 | DW 20 A ; DW 20 B | | 590 | 1850 | 833 | 5634 | TT | | E11-106R-003623 |
| 18.4 - 38 | STANDARD | R2 | 152 A6 | 12 | W 16 | W 15 | 465 | 1800 | 822 | 5579 | TT | 1 | E11-106R-005316 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 21:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..