



TR 273 - Data Sheet



Description

TR 273 is a tractor tire suitable for soil tillage and specifically designed to provide maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning properties. TR 273 perfectly meets all these characteristics.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
12.4 - 24	STANDARD	94054114	R2	117 A8	8	W 11	W 10	12.4	47	21.7	146.5	TT	0	E11-106R-004100
13.6 - 24	STANDARD	94057450	R2	120 A8	8	W 12	W 11	13.8	48.8	22.4	149.4	TT	1	E11-106R-005252
14.9 - 24	STANDARD	94051410	R2	124 A8	8	W 13	W 12	15	51.6	23.4	159.2	TT	0	E11-106R-004514
14.9 - 24	STANDARD	94051427	R2	128 A8	10	W 13	W 12	15	51.6	23.4	159.2	TT	0	E11-106R-004515
18.4 - 26	STANDARD	94057283	R2	142 A8	12	W 16	W 15	18.5	58.7	26.5	178.5	TT	1	E11-106R-005314
23.1 - 26	STANDARD	94055425	R2	152 A6	14	DW 20 A ; DW 20 B		23.2	65.2	29	198.9	TT	0	E11-106R-004628
23.1 - 26	STANDARD	94039784	R2	145 A8	10	DW 20 A ; DW 20 B		23.2	65.2	29	198.9	TT	0	E11-106R-003620
23.1 - 26	STANDARD	94039821	R2	149 A8	12	DW 20 A ; DW 20 B		23.2	65.2	29	198.9	TT	0	E11-106R-003395
14.9 - 28	STANDARD	94054121	R2	126 A8	8	W 13	W 12	15.2	55.5	25.6	172	TT	0	E11-106R-004516
16.9 - 30	STANDARD	94057238	R2	140 A8	12	W 15 L	W 14 L	17.1	60.2	27.8	189	TT	1	E11-106R-005315
18.4 - 30	STANDARD	94042418	R2	145 A8	12	W 16 L	W 15 L	18.3	62.4	28.5	193.9	TT	0	E11-106R-003621
23.1 - 30	STANDARD	94045693	R2	154 A8	14	DW 20 A ; DW 20 B		23.2	68.8	31.3	210.9	TT	0	E11-106R-003645
23.1 - 30	STANDARD	94045716	R2	147 A8	10	DW 20 A ; DW 20 B		23.2	68.8	31.3	210.9	TT	0	E11-106R-003622
18.4 - 34	STANDARD	94055821	R2	146 A8	12	DW 16A	W16L,W15L,DW15L	18.7	67	30.5	206.8	TT	0	E11-106R-004517
23.1 - 34	STANDARD	94045907	R2	157 A8	14	DW 20 A ; DW 20 B		23.2	72.8	32.8	221.8	TT	1	E11-106R-003646
23.1 - 34	STANDARD	94045730	R2	150 A8	10	DW 20 A ; DW 20 B		23.2	72.8	32.8	221.8	TT	0	E11-106R-003623
18.4 - 38	STANDARD	94056590	R2	149 A8	12	W 16	W 15	18.3	70.9	32.4	219.6	TT	1	E11-106R-005316

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 20:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The

user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..