



TR 459 - Data Sheet



Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader • Tractor
Industrial: Backhoe Loader

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/70 - 20	INDUSTRIAL	94051700	R4	149 A8		13	12 SDC ; 13 SDC ; 14	15.9	42.9	0	0	TL	E11-106R-005332
14.9 - 24	INDUSTRIAL	94016440	R4	137 A8	8	DW 13	DW 12 ; DW 11 ; DW 13 L	15.4	49	22.1	144	TL	E11-106R-005281
14.9 - 24	INDUSTRIAL	94016457	R4	145 A8	12	DW 13	DW 12 ; DW 11 ; DW 13 L	15.4	49	22.1	144	TL	E11-106R-005333
16.9 - 24	INDUSTRIAL	94016464	R4	142 A8	8	DW 15 L	DW 14 L	17.7	51.6	23.2	151.6	TL	E11-106R-005188
16.9 - 24	INDUSTRIAL	94016488	R4	145 A8	10	DW 15 L	DW 14 L	17.7	51.6	23.2	151.6	TL	E11-106R-005211
16.9 - 24	INDUSTRIAL	94016495	R4	149 A8	12	DW 15 L	DW 14 L	17.7	51.6	23.2	151.6	TL	E11-106R-003624
17.5L - 24	INDUSTRIAL	94016563	R4	139 A8	8	DW 15 L	DW 14 L	17.5	50	21.9	150.6	TL	E11-106R-005212
17.5L - 24	INDUSTRIAL	94016587	R4	144 A8	10	DW 15 L	DW 14 L	17.5	50	21.9	150.6	TL	E11-106R-005285
17.5L - 24	INDUSTRIAL	94016594	R4	148 A8	12	DW 15 L	DW 14 L	17.5	50	21.9	150.6	TL	E11-106R-004659
18.4 - 24	INDUSTRIAL	94016617	R4	155 A8	12	DW 16 L	DW 15 L	18.6	54.1	24	162	TL	E11-106R-005217
19.5L - 24	INDUSTRIAL	94016662	R4	147 A8	10	DW 16 L		19.3	52.5	23	158.7	TL	E11-106R-005334
19.5L - 24	INDUSTRIAL	94016686	R4	151 A8	12	DW 16 L		19.3	52.5	23	158.7	TL	E4-106R-002300
19.5L - 24	INDUSTRIAL SPECIAL	94035625	R4	151 A8	12	DW 16 L		19.3	52.5	23	158.7	TL	
21L - 24	INDUSTRIAL	94016709	R4	155 A8	12	DW 18 L		21	54.3	23.8	157.3	TL	E11-106R-003625
21L - 24	INDUSTRIAL	94054404	R4	157 A8	14	DW 18 L		21	54.3	23.8	157.3	TL	E11-106R-005366
18.4 - 26	INDUSTRIAL	94016624	R4	156 A8	12	DW 16 L	DW 15 L	18.6	56.1	24.7	171.1	TL	E4-106R-002304
18.4 - 26	INDUSTRIAL	94016631	R4	159 A8	14	DW 16 L	DW 15 L	18.6	56.1	24.7	171.1	TL	E11-106R-003396
18.4 - 26	INDUSTRIAL	94066223	R4	162 A8	16	DW 16 L	DW 15 L	18.6	56.1	24.7	171.1	TL	E11-106R-006635
16.9 - 28	INDUSTRIAL	94016525	R4	145 A8	8	DW 15 L	DW 14 L	17.3	55.5	25.2	163.2	TL	E11-106R-005287
16.9 - 28	INDUSTRIAL	94016532	R4	148 A8	10	DW 15 L	DW 14 L	17.3	55.5	25.2	163.2	TL	E11-106R-005451
16.9 - 28	INDUSTRIAL	94016556	R4	152 A8	12	DW 15 L	DW 14 L	17.3	55.5	25.2	163.2	TL	E11-106R-003626
18.4 - 28	INDUSTRIAL	94016648	R4	157 A8	12	DW 16 L	DW 15 L	18.6	58.1	26.1	177	TL	E4-106R-002830
21L - 28	INDUSTRIAL	94044337	R4	157 A8	12	DW 18 A		21.1	58.3	0	0	TL	E11-106R-005335
16.9 - 30	INDUSTRIAL	94035595	R4	153 A8	12	DW 15 L	DW 14 L	17.3	57.9	25.9	176.5	TL	E11-106R-005288

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..