



## TRAC SUPER - Data Sheet

### Description

TRAC SUPER is the first radial tire introduced in BKT's municipality segment. The steel-belted tire structure ensures an excellent smooth drive combined with best traction performance. As a result, it is particularly suitable for applications on large lawn surfaces such as parks and roadsides.



### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Small Tractor

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
400/50 R 15	STANDARD	118 A8	13.00		380	775	329	2269	370	TL	E11-106R-009073
440/50 R 17	STANDARD	135 D	14.00	13.00	441	872	395	2674	410	TL	E4-106R-000662
500/50 R 17	STANDARD	147 D	16.00		490	940	425	2850	450	TL	E11-106R-007767

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 21:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..